



# 5400 SERIES

## BASIC ROUTER FEATURES

- Industrial robust design and compact metal housing
- High data speed via 5G NR with 4G fallback
- Strong electromagnetic interference resistance, heat endurance and radiation ability
- Supports multiple VPN (IPSec, OpenVPN, VPN Client, GRE, etc.)
- Supports multiple network protocols (ICMP, TCP, UDP, Telnet, SSH, HTTP, HTTPS, etc.)
- Supports multiple functions (DHCP, DNS, DDNS, Firewall, NAT, DMZ host, etc.)
- Built-in watchdog, multi-link detection ensures working in a stable and secure way
- Network failover and failback via Wi-Fi & Wired Internet
- Wi-Fi Built-In, Optional: Wi-Fi Antenna required
- 4xLAN or 3xLAN + 1xWAN
- WAN port support PPPoE, static IP, DHCP client, 4G
- Always online, automatic reboot if disconnected to ensure continual connection
- LCP/ICMP/flow/heartbeat check, to ensure network usability
- Web/CLI/SSH/management platform support, easy to configure
- SNMP network management, NTP support
- Local & remote management (configuration, status, upgrade firmware, ping, reboot)
- Supports Port forwarding and Bridge
- Supports timing operation
- Supports LED status indication
- Shock and vibration resistant
- Control by SMS, email
- Schedule reboot

# SPECIFICATIONS



**Module:** Quectel RM520N-GL  
**Category:** 5G NR (Cat-19 4G Fallback)  
**Carrier Approvals:** Verizon, AT&T, T-Mobile  
**Regulatory Approvals:** FCC/IC, PTCRB, GCF  
**Frequency Bands:** n1,2,3,5,7,8,12,13,14,18,20,25,  
 26,28,29,30,38,40,41,48,66,  
 70,71,75,76,77,78,79  
**Peak Data Speeds LTE:** DL 3.4 Gbps/ UL 550 Mbps

<b>Interface Type:</b>	4x 1 Gbps port (RJ45) LED: "WLAN," "WAN," "LAN," "NET" 4 x SMA-K antenna interface 2 x RP-SMA Wi-Fi interface SIM/UIM: 1.8V/3V Power: "PWR" 5V ~ 30V Reset: "RST"	<b>SIM:</b>	2FF (dual SIM available)
<b>Power Adapter:</b>	Certificate: FCC, UL	<b>Dimensions:</b>	Item (L x W x H): 5.25 x 4.5 x 1.75 inch Packaging (L x W x H): 9.75 x 5.75 x 4.5 inch Item Weight: 0.12 lbs. Packaging: 1.13 lbs total weight including product
<b>Power Consumption:</b>	Idle: <180mA@12VDC Data: <300mA@12VDC Average: 240mA@12VDC	<b>Certificates:</b>	FCC, ISO, CE, RoHS
<b>Physical:</b>	Operating Temperature Storage: -40°C to 85°C Working: -30°C to 75°C Humidity: 95% maximum (non-condensing)	<b>Package Content:</b>	5400 - 4 Port Router CAT5 Ethernet Cable Power Adapter 4 x Cellular Antenna - Mag Mount 1 SIM
		<b>Wi-Fi:</b>	Optional